J2 FLOORING®

Technical Data Sheet

RUSTIC TEXTURES

Collection Name	-	Rustic Textures Collection
Size	-	Various (see second sheet for formats)
Thickness	ISO 24346	2.0mm (-0.10mm, +0.13mm)
Wear Layer	ISO 24340	0.30mm ± 0.02mm
Bevelled Edge	-	Micro Bevel
Pack Size	-	Various (see second sheet for quantity)
Installation Method	-	Glue Down
Recommended Adhesive	F. Ball, Uzin	F46, F48, KE66, KE2000S
Surface Treatment	-	PU Coating
Wear Guarantee	-	Commercial 5-7 Years* Residential 12 Years
Total Mass Per Area	ISO 23977	3293g/m2
Reaction to Fire	EN 13501-1	Bfl-S1
Fire Rating **Flame Spread** **Smoke Evolution**	 ASTM E648 ASTM E662	 Class I (> 0.45 W/cm2) Class I (<450)
Classification	ISO 10874	31 Commercial (Moderate) 23 Domestic (Heavy)
Dimensional Stability	BS EN ISO 23999	<0.12%
Slip Resistance	BS 7976	Low Slip Potential (36+) Plank PTV 62 (dry), 55 (wet)
Acoustic Impact Sound Reduction	BS EN ISO 10140-3:2021	1dB Reduction
Abrasion Resistance	ASTM 4060	Pass > 1800 cycles
Thermal Resistance	EN 12667:2001	0.05 W/mK
	Underfloor Heating	Suitable Max 27oC
Residual Indentation	ISO 24343-1	Pass <0.1mm
Castor Chair Continuous Use	ISO 4918 / EN 425	18000 cycles
Staining Resistance	EN 438-2	Grade 5
Resistance to Light	EN ISO 105-B02	Pass ≥ 6
Phthalate Free	-	Yes
Formaldehyde / Toxicity	EN71-3=1:2004	Non-Toxic
VOC'S	Floorscore	Certified
Indoor Air Comfort	ISO 9001:2015	Gold
Recycling		Suitable
Cleaning and Maintenance	Dr Schutz	Clean and Strip, PU Cleaner, Floor Cleaner R1000.

*Commercial Wear warranty is subject to location and usage, contact j2 Flooring to discuss the suitability for your project

EPD®
THE INTERNATIONAL EPD® SYSTEM

For more Information

Unit 2 Barracuda Way
Burscough
Lancashire
L40 7BP

Tel: 01704 536421
Email: sales@j2flooring.com

www.j2flooring.com

J2 FLOORING®

Technical Data Sheet

RUSTIC TEXTURES

		LRV Value	Format Availability	
Collection	Colour Name and Code	LRV Score Standard: BS8493	Plank 914mm x 152mm	Herringbone 400mm x 100mm
	Pack Quantity		3.34m2	2.56m2
Rustic Textures	**Golden Oak 02**	20		
	Grey Driftwood 16	33		
	Silver Ash 17	26		
	Select Oak 22	34		
	Studio Timber 23	31		
	New Forest Oak 24	29		

*Commercial Wear warranty is subject to location and usage, contact j2 Flooring to discuss the suitability for your project

EPD®
THE INTERNATIONAL EPD® SYSTEM

For more Information

Unit 2 Barracuda Way
Burscough
Lancashire
L40 7BP

Tel: 01704 536421

Email: sales@j2flooring.com

www.j2flooring.com