J2 FLOORING®

Technical Data Sheet

STRATA

Size	-	**Plank** 1220mm x 183mm **Tile** 600mm x 300mm
Thickness	ISO 24346	8.0mm
Wear Layer	ISO 24340	0.50mm
Pack Size	-	**Plank** 1.79m2 (8 Planks) **Tile** 1.44m2 (8 Tiles)
Bevelled Edge	-	**Plank** Full Bevel **Tile** Painted Bevel
Underlay	-	Built in IXpe Underlay
Installation Method	Click System	Uniclic (Unilin)
Surface Treatment	-	PU Coating
Wear Guarantee	-	**Commercial** 10 Years* **Residential** Lifetime (30 Years)
Total Mass Per Area	ISO 23977	13,190g/m2
Reaction to Fire	EN 13501-1	Bfl-S1
Classification	ISO 10874	33 Commercial (Heavy) 23 Domestic (Heavy)
Dimensional Stability	EN 434	<0.17%
Peel Strength	EN 431	Pass 75N/50mm
Slip Resistance	BS-EN-16165:2021/22	Low Slip Potential (36+) Plank PTV 60 (dry), 38 (wet) Tile PTV 65 (dry), 49 (wet)
Acoustic Impact Sound Reduction	BS EN ISO 10140-3:2021	19dB Reduction
Abrasion Resistance	ASTM 4060	Pass > 4500 cycles
Impact resistance	EN 13329	Pass >1800
Thermal Resistance	EN 12667:2001	0.05 W/mK
	Underfloor Heating	Suitable Max 27oC
Residual Indentation	ISO 24343-1	Pass <0.1mm
Staining Resistance	ISO 26987	Pass
Resistance to Light	EN ISO 105-B02	Pass > 6.5
Phthalate Free	-	Yes
Formaldehyde / Toxicity	EN71-3=1:2004	Non-Toxic
VOC'S	Floorscore	Certified
Indoor Air Comfort	ISO 9001:2015	Gold
Recycling		Suitable

*Commercial Wear warranty is subject to location and usage, contact j2 Flooring to discuss the suitability for your project

EPD®
THE INTERNATIONAL EPD® SYSTEM

For more Information

Unit 2 Barracuda Way
Burscough
Lancashire
L40 7BP

Tel: 01704 536421

Email: sales@j2flooring.com

www.j2flooring.com